

1

2

3

4

D

C

B


A

BREAK SHARP CORNERS MAY BE EITHER CHAMFER OR RADIUS FROM 0.2 mm MIN. TO 1.0 mm MAX.

THIS DRAWING IS A SOLE PROPERTY OF M & M I t d. IT SHOULD NOT BE REPRODUCED IN ANY FORM OR BY ANY MEANS WITHOUT THEIR CONSENT

REFER DRAWING :- 007537394C91

REF PART NO: 007537394C91

UNSPECIFIED TOLERANCES FOR PART		SURFACE FINISH SYMBOLS:ISO-1302				MAHINDRA & MAHINDRA LTD. FARM DIVISION, INDIA		
FORMING TO FORMING	UPTO 500 ±0.5 ABOVE 500 ±0.8	WELDING SYMBOLS:IS813						
CD BETWEEN HOLES	IN ONE PLANE ±0.2 IN DIFF PLANES±0.5	REMOVE ALL SHARP CORNERS & BURRS						
FORM TO PIERCE	±0.5	DO NOT SCALE ALL DIMENSIONS ARE IN mm	<SC> COUNT : 0	NAME	DATE	PROJECT CODE:		
HOLE SIZES	+0.2/-0		<CC> COUNT▽ 0	DSNR	AR	07-06-2023	ER NUMBER: ER23C0000228	
SLOT SIZES	±0.8		WEIGHT(kg) :	CHKR	NVC	07-06-2023	DESCRIPTION :	
FLANGE WIDTH	+1.0/-0.7		S/F AREA(cm²):	APPR	DS	07-06-2023	CHANNEL SUPPORT RH ASSY	
JOGGLE DEPTH	+0.3/0		MATERIAL:			PART NUMBER :		CL:
UNSPECIFIED TOLERANCES FOR PART & ASSEMBLY			REFER BOM			008032636U01		NA
GENERAL TOLERANCES	UP TO 300 ±0.8 ABOVE 300 ±1.0			DWG.SIZE : A4		SCALE :	1:1	SHEET: 1 OF 1
ANGULAR TOLERANCE	±1°							

CHECK DRAWING WITH LATEST CHANGE No

DO NOT CHANGE MANUALLY

COMPUTER GENERATED DRAWING

4